HD31033
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class AB linear design
Instantaneous wide bandwidth
Suitable for all modulations standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	1.2 - 1.4 GHz	
Power Output Psat	250 Watt Min	CW
Output Power @ P1dB	180 Watt Min	
Power Gain	54 dB Min	
Power Gain Flatness	2.0 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30dBc Typ	44 dBm/Tone, Δ = 1MHz
Harmonics	>20 dBc Typ	At rated Pout
Non Harmonics Spurious	>60 dBc	
Operating Voltage	28 - 30 VDC	
Current Consumption	24 Amp Max	At rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	∞ : 1	
Turn On / Off Speed	5 µSec Max	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	220 X 156 X 27 mm	Excluding Connectors
Weight	1525 gr.	Max Weight
RF Connectors In/Out	SMA female / Type N female	
DC Power / Interface Connector	7W2 - 7-Pin Hybrid D-Sub	
Cooling	External Heatsink	Forced air required


D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	OPTION 101 - Forward power detect
2	VVA	OPTION 103 - Variable Voltage Attenuator
3	CURRENT SENSOR	I_D@20mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	TTL
A1	VDD	28VDC
A2	GND	Ground

332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
sales@rfamplifiers.com www.rfamplifiers.com

HD31033
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
sales@rfamplifiers.com www.rfamplifiers.com