HD31927
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class AB linear GaAsFET hybrid design
Instantaneous bandwidth
Suitable for all single channel modulation standards
Built-in protection circuits
High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	41.0 - 47.0 GHz	
Power Output Psat	2 Watt Min	
Power Output @ P1dB	1 Watt Typ	
Power Gain	33 dB Min	
Power Gain Flatness	4.0 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
Noise Figure	12 dB Max	
Harmonics	-20 dBc Max	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	9 VDC Nom	
Current Consumption	5 Amp Max	At rated Pout
Max Input Power Protection	+3 dBm	<10 Sec without damage
Load VSWR Protection	5 : 1	<1 minute @ rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +65 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	60 x 70 x 20 mm	Excluding connectors
Weight	TBD	
RF Connectors In/Out	SMA K Type female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	N/C	Reserved
2	N/C	Reserved
3	CURRENT SENSOR	I_D@20mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	TTL
6,7	VDD	9VDC
8,9	GND	Ground

332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfamplifiers.com www.rfcomp.com sales@hdcom.com