HD Communications Corp.

HD32043
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Rack mounted system
Class AB linear GaN design
Instantaneous wide bandwidth
Suitable for all single channel modulation standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	0.5 - 2.5 GHz	
Power Output @ Saturation	500 Watt Min	CW
Power Output @ P1dB GCP	200 Watt Min	
Power Gain	57 dB Min	
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	47dBm/Tone, Δ = 1MHz
Harmonics	>20 dBc Typ	At rated output power
Non Harmonics Spurious	60 dBc Min	
Operating Voltage	180 - 240 VAC	
Power Consumption	3 KW Max	At rated Pout
Max Input Power	+8 dBm	Note 1
Load VSWR Protection	∞ : 1	Note 2

Notes:

1. Nominal Input Power is 0dBm. +8dBm is allowed for up to 10Sec with no damage.
2. 1 Minute Max @ rated min Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensing

MECHANICAL SPECIFICATIONS


Parameter	Specification	Notes
Dimensions W x H x D	5U Rack Mount Chassis	See outline drawing
Weight	35 Kg	
RF Connectors In / Out	Type-N Female	Front Panel Standard
AC Power / Interface	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control: FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, Optional GPIB Interface	Remote Bluetooth application

332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.com www.rfamplifiers.com sales@hdcom.com

HD32043
SOLID STATE HIGH POWER AMPLIFIER

Communications Corp.

OUTLINE DRAWING



332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.com www.rfamplifiers.com sales@hdcom.com