HD32129
SOLID STATE PULSE HIGH POWER AMPLIFIER

FEATURES

High power GaN pulse devices
Suitable for X-Band linear pulse applications
Built-in Ethernet Control and Protection circuits
High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification			Notes
Operating Frequency Range	9.2 - 10 GHz			
Peak Output Power	8000 Watt Min			5% Duty Cycle
Input Power	+9 dBm Nom			Pulsed for normal opertion
Saturated Gain	60 dB Min			
Gain Adjustment Range	20 dB Min			
Power Gain Flatness	2 dB p-p Max			
Gain Stability	0.5 dB p-p Max			Constant Temperature
Pulse Characteristics	**Duty**	**Width**	**PRF**	
	5 % Max	0.2 - 50 µSec	10 KHz Max	
Pulse Droop	0.5 dB Max			@ 50 µSec
Rise / Fall Time	50 nSec			
Input / Output VSWR	2 : 1 Min			Relative to 50 Ohm
Harmonics	-10 dBc Max			
Spurious	-50 dBc Max			Non-harmonics
Noise Figure	35 dB Max			
Load VSWR Protection	2.5 : 1			Without damage
Maximum Input Power Protection	+13 dBm Max			<10Sec
Gate Control Inputs	TTL - gating pulse must precede RF by 2 µSec			
AC Input Voltage	230 VAC, 1 Phase, 50 - 60 Hz			
RF Output Sample	-60 dB			RF output

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50°C	
Vibrations	MIL-STD 810G, Method 514.6	
Altitude	10,000 feet	30,000 feet non-operating
Relative Humidity	Up to 95 %	Non-condensing


MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	See preliminary outline drawing	12U, 19” rack
Weight	TBD	
RF Input Connector	SMA (F) Jack	
RF Output Connector	WR-90 Waveguide flange	Waveguide pressure sensor
RF Sample Port	SMA (F) Jack	
AC Power	MS3122E14-5P	or similar
Transmit Gating Connector	BNC-F	
Monitor & Control	Ethernet RJ-45 circular connector TCP/IP RS422/485 D-sub 9S port for redundancy	
Cooling	Built in Fan Cooling	Front Inlet, Rear outlet

332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.comwww.rfamplifiers.comsales@hdcom.com

HD32129
SOLID STATE PULSE HIGH POWER AMPLIFIER

OUTLINE DRAWING



332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.comwww.rfamplifiers.comsales@hdcom.com