HD33635
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class A/AB linear GaN design
Instantaneous bandwidth
Suitable for all single channel modulation standards
Small form factor, light weight
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50 Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	5.0 - 5.4 GHz	
Power Output @ Psat	60 Watt Typ	CW
Power Output @ P1dB	50 Watt Min	
Power Gain	48 dB Min	
Power Gain Flatness	2.0 dB p-p Max	Constant input power
Input / Output Return Loss	-10 dB Max	
2-Tone Intermodulation (IMD)	<-30 dBc Typ	37dBm/Tone, Δ = 1 MHz
Harmonics	<-20 dBc Typ @ 30W	-11dBc Typ below 1GHz
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	30 VDC Nom	
Current Consumption	11 Amp Max	At rated Pout
Input Power Protection	+8 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	230 (260[1]) x 106 x 27 mm	Excluding connectors
Weight	1.25 Kg.	
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	OPTION 101 - Forward power detect
2	VVA	OPTION 103 - Variable Voltage Attenuator
3	CURRENT MONITOE	I_D @ 20mV/100mA Typ
4	TEMP MONITOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	Enable: TTL “Hi” or Open / Disable: TTL “Lo” or Short
6, 7	VDD	30VDC
8, 9	GND	Ground


HD Communications Corp. 338 Jericho Tpke. Ste 387
Syosset, NY 11791
Tel: (631) 588-3877 Email: sales@hdcom.com

HD33635
SOLID STATE HIGH POWER AMPLIFIER


Notes:

1. Length with Options 101 & 103

OUTLINE DRAWING



OUTLINE DRAWING WITH OPT 101 &103



HD Communications Corp. 338 Jericho Tpke. Ste 387
Syosset, NY 11791
Tel: (631) 588-3877 Email: sales@hdcom.com