HD30498
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Designed for EMC-EMI/RFI, Lab, and general comm applications
Compact Small form factor, light weight, high power density
Class A/AB linear advanced technology design
Instantaneous ultra-wide bandwidth
Suitable for all single channel modulation standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	500 - 3000 MHz	
Power Output @ Psat	25 Watt Min	CW
Power Gain	44 dB Min	0dBm or less for rated Pout
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	34dBm/Tone, Δ = 1MHz
Harmonics	<-20 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	28 - 30 VDC	
Current Consumption	4 Amp Max / <3 Amp Typ	At rated Pout
Input Power Protection	+8 dBm Max	<10 Sec without damage
Load VSWR Protection	∞ : 1	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport[1]	

1 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	166 x 69 x 27 mm	Excluding connectors
Weight	600 gr.	
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required


D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	Option-101
2	REV	Option-102
3	CURRENT SENSOR	I_D@50mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	Enable = TTL High, or Open; Disable = TTL Low or Short
6, 7	VDD	28VDC
8, 9	GND	Ground

38 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com
Specifications subject to change without notice. Specifications and drawings may vary with selected options.

HD30498
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



38 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com

Specifications subject to change without notice. Specifications and drawings may vary with selected options.