HD30780
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class AB linear LDMOS design
Instantaneous ultra-wide bandwidth
Suitable for all single channel modulation standards
Small form factor and light weight
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25 °C

Parameter	Specification	Notes
Operating Frequency Range	0.25 - 1000 MHz	
Power Output @ Psat	10 Watt Min	CW
Power Gain	40 dB Min	
Power Gain Flatness	4 dB p-p Max	Constant input power
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	<-30 dBc Typ	30dBm/Tone, Δ = 1MHz
Harmonics @ Rated Pout (2^{nd}/ 3^{rd})	-14 dBc Typ	Below 500 MHz
	-20 dBc Typ	
Spurious	-60dBc Max	Non-harmonics
Noise Figure	<10 dB Typ	
Operating Voltage	28 - 30 VDC	
Current Consumption	2 Amp Max	At rated Pout
Max Input Power	+8 dBm	<10 Sec without damage
Load VSWR Protection	∞ : 1	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	125 x 63 x 27 mm	Excluding connectors
Weight	350 gr.	
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required


D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	N/C	N/C
2	VVA	Option-103 (With larger housing dimensions)
3	CURRENT SENSOR	I_D@50mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	Enable = TTL High or Open; Disable = TTL Low or Short
6, 7	VDD	28VDC
8, 9	GND	Ground

338 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com
Specifications subject to change without notice. Specifications and drawings may vary with selected options.

HD30780
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



338 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com

Specifications subject to change without notice. Specifications and drawings may vary with selected options.