HD31017
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Small and light weight bench top chassis
Class AB linear GaAs FET design
Instantaneous bandwidth
Suitable for all single channel modulation standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25ºC

Parameter	Specification	Notes
Operating Frequency Range	30.0 - 40.0 GHz	
Power Output @ Psat	5 Watt Min	CW
Power Gain	37 dB Min	
Power Gain Flatness	6.0 dB p-p Max	At rated Pout
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	27dBm/Tone, Δ = 1MHz
Harmonics	-25 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Noise Figure	10 dB Max	
Operating Voltage	100 - 240 VAC	47/63Hz
Power Consumption	300 Watt Max	At rated Pout
Input Power Protection	+3 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 ºC	
Storage Temperature	-40 to +85 ºC	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS


Parameter	Specification	Notes
Dimensions W x H x D	210 x 100 x 300 mm	Excluding brackets
Dimensions W x H x D (Benchtop)	242 x 110 x 384 mm	Including brackets
Weight	8 kg.	
RF Connectors In/Out	2.9 mm (K / air type) Female	Front Panel Standard
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
OPTIONAL: Digital Monitor & Control (DMC) FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, **OPTIONAL**: Safety Interlock	Ethernet RJ-45 TCP/IP, RS422/485, USB Open=STBY/Short=RFON	Requires larger 3U chassis. BNC Female on rear panel

338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.

HD31017
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.