
HD31089
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class A/AB linear design
High Power Advanced technology devices
Instantaneous wide bandwidth
Suitable for all single channel modulation standards
Small form factor & light weight
Built-in monitoring & protection circuits
High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	8.0 - 12.0 GHz	
Power Output @ Psat	100 Watt Min / 120 Watt Typ	CW
Power Gain	50 dB Min	0dBm or less for rated Pout
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input Return Loss	-10 dB Max	
Harmonics	-25 dBc Max	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Noise Figure	10 dB Max	
Operating Voltage	32 VDC Nom	
Current Consumption	23 Amp Max / <20 Amp Typ	At rated Pout
Input Power Protection	+3 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	< 1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport[1]	

1 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	180 x 200 x 27 mm	Excluding connectors
Weight	4 Kg.	
RF Connectors In/Out	SMA female / Type-N female	
DC Power / Interface Connector	7-Pin Hybrid D-Sub	
Cooling	External Heatsink[2]	Forced air required

2. Proper cooling is require to insure thermal rise doesn't exceed the specified operating case temperature due to module power & power consumption.


D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	N/A	N/A
2	N/A	N/A
3	CURRENT SENSOR	I_D@20mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	Enable = TTL "High" (>3.2V) or Open / Disable = TTL "Low" or Short
A1	VDD	32VDC
A2	GND	Ground

338 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com
Specifications subject to change without notice. Specifications and drawings may vary with selected options.

HD31089
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



338 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com

Specifications subject to change without notice. Specifications and drawings may vary with selected options.