HD31773
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class A/AB linear design
High Power Advanced technology devices
Instantaneous wide bandwidth
Suitable for all single channel modulation standards
Small form factor & light weight
Built-in monitoring & protection circuits
High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	3.0 - 6.0 GHz	
Power Output @ Psat	100 Watt Min	CW
Power Output @ P1dB	60 Watt Typ	CW
Power Gain	50 dB Min	0dBm or less for rated Pout
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	40dBm/Tone, Δ = 1 MHz
Harmonics	-20 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	28 VDC Nom	
Current Consumption	24 Amp Max	At rated Pout
Max Input Power	+3 dBm Max	<10 Sec without damage
Load VSWR Protection	10 : 1[1]	<1 minute at rated Pout

1 Modules could be damaged due to excessive VSWR beyond 1 minute

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +65 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport[2]	

2 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	260 x 200 x 27mm	Excluding connectors
Weight	3.2 Kg.	
RF Connectors In/Out	SMA female / Type-N female	
DC Power / Interface Connector	9-Pin Hybrid D-Sub	9W4
Cooling	External Heatsink	Forced air required


38 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com
Specifications subject to change without notice. Specifications and drawings may vary with selected options.

HD31773
SOLID STATE HIGH POWER AMPLIFIER

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	N/C	N/C
2	N/C	N/C
3	CURRENT SENSOR	I_D@20mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	Enable = TTL High or Open; Disable = TTL Low or Short
A1, A2	VDD	28VDC
A3, A4	GND	Ground

OUTLINE DRAWING



38 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com
Specifications subject to change without notice. Specifications and drawings may vary with selected options.