HD33757
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all communication applications
Small form factor, rack mounted Dual-Band system
Class A/AB Linear design
High Power Advanced technology devices
Instantaneous ultra-wide bandwidth
Built-in protection circuits, with extensive monitoring
Local LCD & remote flexible interfaces
High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25°C

Parameter	Specification		Notes
Band	**Band A**	**Band B**	Band switching @ 15mS Max
Operating Frequency Band	1.0 - 6.0 GHz	6.0 - 18.0 GHz	
Power Output @ Psat	20 Watt Typ		CW or Pulse
Power Output @ P1dB	15 Watt Min		
Power Gain	43 dB Min		0dBm or less for rated power
Power Gain Flatness	4.0 dB p-p Max	5.0 dB p-p Max	Constant input power
Gain Adjustment Range	20 dB Min		Local or remote capable
Input Return Loss	-10 dB Max		
2-Tone Intermodulation (IMD) Band A / Band B	-30 dBc Typ		33dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ		At rated Pout
Spurious	-60 dBc Max		Non-harmonics
Operating Voltage	100 - 240 VAC		47-63Hz
Power Consumption	500 Watt Max		At rated Pout
Input Power Protection	+10 dBm Max[1]		
Load VSWR Protection	4 : 1: Max[2]		Foldback @ preset limit
Sample Port (optional)	-40 dB		N-Female

1 Units with optional digital monitor and control, for basic units <10 Sec without damage
2 Units with optional digital monitor and control, for basic units <1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non Condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport[3]	

3 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 560 mm	3U, excluding handles
Weight	17 kg.	
RF Conn. In / Out / Sample (optional)	N-Female	Front or rear panel
Interface Connector	9-Pin D-Sub	Rear panel
AC Power	IEC 60320-C14	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
STANDARD: Digital Monitor & Control[4] FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, **OPTIONAL**: Safety Interlock	Ethernet RJ-45 TCP/IP, RS422/485, USB Open=STBY/Short=RFON	 BNC Female on rear panel

4 Option DMC, LCD controller option may reduce output power by up to -0.5dB

338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.


HD33757
SOLID STATE HIGH POWER AMPLIFIER

AVAILABLE SPECIAL OPTIONS

Parameter	Specification	Notes
Option FRS: Forward RF Sample	-40dB, Type N-Female	Front or rear panel
Option RRS: Reflected RF Sample	-40dB, Type N-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring (With purchase of Option DMC)	Offset correction entry for +/- 0.2dB accuracy	10-points standard[5]

5 Consult with factory if additional points would be required.

OUTLINE DRAWING
SHOWN WITH OPTIONAL LCD DIGITAL CONTROLLER



338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.