
HD34622
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all communication applications
Small form factor, rack mounted system
Class A/AB linear design
High power Advanced technology devices
Instantaneous wide bandwidth
Built-in protection circuits, forward RF Sample port
High reliability and ruggedness with extensive monitoring
Remote-control platforms included
High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25?C

Parameter	Specification	Notes
Operating Frequency Range	18.0 - 40.0 GHz	
Power Output @ Psat	10 Watt Min / 15 Watt Typ	CW or Pulse
Power Output @ P1dB	5 Watt Typ	
Power Gain	40 dB Min	0dBm or less for Rated Power
Power Gain Flatness	4.0 dB p-p Max	Constant input power
Gain Adjustment Range	20 dB Typ	Local or remote capable
Input Return Loss	-10 dB Max	
2-Tone Intermodulation (IMD)	-30 dBc Typ	30dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Max	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	47 - 63Hz
Power Consumption	500 Watt Max	At rated Pout
Input Power Protection	+5 dBm Max[1]	
Load VSWR Protection	4 : 1: Max[2]	Foldback @ preset limit

1 Units with optional digital monitor and control, for basic units <10 Sec without damage
2 Units with optional digital monitor and control, for basic units <1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport[3]	

3 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 750 mm	3U, excluding handles
Weight	20 kg.	
RF Connectors In / Out / Sample Port	2.9 mm-F / WRD180 / 2.9mm-F	Front or rear panel
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling: Built in Quiet-Cool	Close circuit Air-liquid cooling	Air cooled
STANDARD: Digital Monitor & Control[4] FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, **OPTIONAL**: Safety Interlock	Ethernet RJ-45 TCP/IP, RS422/485, USB Open=STBY/Short=RFON	 BNC Female on rear panel

4 DMC option may reduce Pout by 1dB.

338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com
Specifications subject to change without notice.
Specifications and drawings may vary with selected options.


HD34622
SOLID STATE HIGH POWER AMPLIFIER

AVAILABLE SPECIAL OPTIONS

Parameter	Specification	Notes
Option FRS: Forward RF Sample	-40dB, Type K-Female	Front or rear panel
Option RRS: Reflected RF Sample	-40dB, Type K-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring (With purchase of Option DMC)	Offset correction entry for +/- 0.2dB accuracy	12-points standard[5]

5 Consult with the factory if additional points would be required.

OUTLINE DRAWING
SHOWN WITH LCD DIGITAL CONTROLLER



338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.