
HD35115
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Designed for EMC-EMI/RFI, Lab, and general comm applications.
Compact small form factor, light weight, high power density
High power advanced linear GaN device design
Designed for narrow C-Band linear applications.
Suitable for all single channel modulation standards
Built-in protection circuits



ELECTRICAL SPECIFICATIONS : 50Ω, 25?C

Parameter	Specification	Notes
Operating Frequency Range	4.0 - 8.0 GHz	
Power Output @ Psat	200 Watt Min	CW
Power Gain	53 dB Min	0dBm or less for rated Pout
Power Gain Flatness	10.0 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	
2-Tone Intermodulation (IMD)	-30 dBc Typ	43dBm/Tone, Δ = 1MHz
Harmonics	-15 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	32 VDC Nom	
Current Consumption	46 Amp Max	At rated Pout
Max Input Power	+2 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport[1]	

1 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	270 x 200 x 27mm	Excluding connectors
Weight	3.2 Kg.	
RF Connectors In/Out	SMA / Type-N female	
DC Power / Interface Connector	Hybrid 9-Pin D-Sub	9W4
Cooling	Liquid cooling only	Air cooling not allowed


D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	N/A	N/A
2	N/A	N/A
3	CURRENT SENSOR	I_D@10mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	Enable = TTL "High" or Open; Disable = TTL "Low" or Short
A1, A2	VDD	32VDC
A3, A4	GND	Ground

338 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com
Specifications subject to change without notice. Specifications and drawings may vary with selected options.

HD35115
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



338 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com
Specifications subject to change without notice. Specifications and drawings may vary with selected options.