HD35144
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all EW communication applications
Small form factor, rack mounted system
Class A/AB Linear design
High Power Advanced technology devices
Instantaneous ultra-wide bandwidth
Built-in protection circuits, with extensive monitoring
Local LCD & remote flexible interfaces
High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification			Notes	
Operating Frequency Range	500 - 2000 MHz				
Power Output @ Psat	200 Watt Min			CW	
Power Gain	53 dB Min			Pin = 0dBm for rated Pout	
Power Gain Flatness	3.0 dB p-p Max			Constant input power	
Input / Output Return Loss	-10 dB Max			Relative to 50 Ohm	
2-Tone Intermodulation (IMD)	-30 dBc Typ			40dBm/Tone, Δ = 1MHz	
Harmonics	-20 dBc Typ			At rated output power	
Spurious	-60 dBc Max			Non-harmonics	
Operating Voltage	100 - 240 VAC				
Power Consumption	1500 Watt Max			At rated output	
Input Power Protection	4 : 1: Max[2]				
Load VSWR Protection	4 : 1: Max[2]			Foldback @ preset limit	
Pulse Characteristics	**Width**	**Duty**	**PRF**	**Rise/Fall**	**Droop**
	0.1 - 100µS	0 - 100%	0 - 100KHz	25nS Nom	0.5dB Max
Pulse to Pulse Jitter / Pulse Width Jitter / Delay	±5 nS / ±5 nS / 500 nS				
Pulse On / Off Ratio	80 dB Min				

1 Units with optional digital monitor and control, for basic units <10 Sec without damage
2 Units with optional digital monitor and control, for basic units <1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non Condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport[3]	

3 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 560 mm	3U, excluding handles
Weight	20 kg.	
RF Connectors In/Out	Type-N Female	
Pulse Blanking / Safety Interlock	BNC Female	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
STANDARD: Digital Monitor & Control[4] FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, **OPTIONAL**: Safety Interlock	Ethernet RJ-45 TCP/IP, RS422/485, USB Open=STBY/Short=RFON	 BNC Female on rear panel

4 DMC option may reduce Pout by 1dB.

338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.


HD35144
SOLID STATE HIGH POWER AMPLIFIER

AVAILABLE SPECIAL OPTIONS

Parameter	Specification	Notes
OPTIONAL: TTL Pulse Modulator	On / Off @ -80 dBm/Hz	
Option FRS: Forward RF Sample	-40dB, Type N-Female	Front or rear panel
Option RRS: Reflected RF Sample	-40dB, Type N-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring (With purchase of Option DMC)	Offset correction entry for +/- 0.2dB accuracy	7-points standard[4]

4 Consult with factory if additional points would be required.

OUTLINE DRAWING
SHOWN WITH OPTIONAL LCD DIGITAL CONTROLLER



338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.