HD35194
SOLID STATE HIGH POWER PULSE AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, HIRF/Pulse applications
Small form factor rack-mounted system
Class AB linear Advanced technology design
Instantaneous S-band bandwidth
Linear high peak pulse applications
Built-in protection circuits with extensive monitoring
Local LCD & remote flexible interfaces
High efficiency with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25°C

Parameter	Specification			Notes	
Operating Frequency Range	2.0 - 4.0 GHz				
Power Output @ Pulse	8.0 KW Typ			Peak Pulse	
Input Pulse Characteristics	**Width**	**Duty**	**PRF**	**Rise/Fall**	**Droop**
	up to 100 µS	6 % Max	up to 100 KHz	<50 nS Typ	<1 dB
Power Gain	69 dB Min			0dBm or less for rated Pout	
Power Gain Flatness	5.0 dB p-p Max			Constant input power	
Gain Adjustment Range	20 dB Min			Local or remote capable	
Input Return Loss	-10 dB Max				
Output Power On/Off Ratio	-80 dB Min			TTL Gate Control	
Harmonics	-20 dBc Typ			At rated output power	
Spurious	-60 dBc Max			Non-harmonics	
Operating Voltage	200 - 240 VAC, 50-60Hz			Opt: 120/208VAC, 3-Ph	
Power Consumption	4000 Watt Max			At rated Pout	
Input Power Protection	+8 dBm Max[1]				
Load VSWR Protection	4 : 1: Max[2]			Foldback @ preset limit	
Sample Port (optional)	-60 dB			N-Female	

1 Units with optional digital monitor and control, for basic units <10 Sec without damage
2 Units with optional digital monitor and control, for basic units <1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non Condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport[3]	

3 MIL Spec available for quotation

338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com
Specifications subject to change without notice.
Specifications and drawings may vary with selected options.

HD35194
SOLID STATE HIGH POWER PULSE AMPLIFIER

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	See Outline	13U or 14U in rack
Weight	250 lbs. Nom.	<350 lbs rack integrated
RF Connectors In/Out/Sample	RF Input Type-N Female RF Output SC or 716 Female RF Sample Type-N Female	Front panel Rear panel Front panel
Gate Control	BNC Female	Front panel
Interface Connector	9-Pin D-Sub	Rear panel
AC Power	MS	Or equivalent
Cooling: Built in Quiet-Cool	Close circuit Air-liquid cooling	
OPTIONAL: Digital Monitor & Control (DMC) FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, Optional Safety Interlock (INT)	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface Open=STBY/Short=RFON	IEEE rear panel BNC-F rear panel

AVAILABLE SPECIAL OPTIONS

Parameter	Specification	Notes
Option RI: Rack Cabinet Integration	13U standard rack height	Alternate height TBQ
Option FRS: Forward RF Sample	-70dB, Type N-Female	Front or rear panel
Option RRS: Reflected RF Sample	-60dB, Type N-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring (With purchase of Option DMC)	Offset correction entry for +/- 0.2dB accuracy	7-points standard[4]

4 Consult with factory if additional points would be required.

338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.


HD35194
SOLID STATE HIGH POWER PULSE AMPLIFIER


OUTLINE DRAWING


System Outline in 14U Rack Cabinet


SHOWN WITH LCD DIGITAL CONTROLLER

1. Rack : SR14UBDP
   - 14U Rack
2. CONTROL / POWER SUPPLY : 3U
3. HPA SYSTEM : 6U
4. COOLING SYSTEM : 4U
5. Blanking Panel : 1U
6. UNIT : mm / [inch]









338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.