HD35243
SOLID STATE MEDIUM POWER AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all communication applications.
Small form factor, Bench Top system
Class A linear advanced technology design
Suitable for all single channel modulation standards
Instantaneous ultra-broad bandwidth
Built-in protection circuits
Universal voltage AC power supply
High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	18 - 40 GHz	
Power Output @ Psat (CW)	27 dBm Min	<0 dBm for rated Pout
Linear Gain	30 dB Min / 40 dB Max	0dBm or less for rated Pout
Power Gain Flatness	±3.0 dB Typ / ±4.0 dB Max	Constant input power
Input Return Loss	-10 dB Typ	
Noise Figure	8 dB Max / 6 dB Typ	
Harmonics	-20 dBc Max	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	47-63 Hz
Power Consumption	50 Watt Max	At rated Pout
Input Power Protection	+8 dBm Max	Without damage
Load VSWR Protection	∞ : 1	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +70 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport	

MECHANICAL SPECIFICATIONS


Parameter	Specification	Notes
Dimensions W x H x D (Benchtop)	210 x 100 x 300 mm 242 x 110 x 384 mm	Excluding brackets Including brackets
Weight	8 kg.	
RF Connectors In/Out	2.9 mm (K / air type) Female	Front panel standard
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	
OPTIONAL: Digital Monitor & Control (DMC) FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, **OPTIONAL**: Safety Interlock	Ethernet RJ-45 TCP/IP, RS422/485, USB Open=STBY/Short=RFON	Requires larger 3U chassis. BNC Female on rear panel

338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.

HD35243
SOLID STATE MEDIUM POWER AMPLIFIER

OUTLINE DRAWING



338 Jericho Tpk, Unit 387 Syosset, NY 11791 Phone: 631-588-3877
www.rfamplifiers.com sales@hdcom.com www.rfcomp.com

Specifications subject to change without notice.
Specifications and drawings may vary with selected options.