# HD35284
# SOLID STATE MEDIUM POWER AMPLIFIER

**FEATURES**

Designed for EMI/RFI, lab, CW/Pulse and all communication applications.
Small form factor, Bench Top system
Class A linear advanced technology design
Suitable for all single channel modulation standards
Instantaneous ultra-broad bandwidth
Built-in protection circuits
Universal voltage AC power supply
High efficiency, with unprecedented reliability and ruggedness



**ELECTRICAL SPECIFICATIONS** : 50Ω, 25ºC

| Parameter | Specification | Notes |
|---|---|---|
| Operating Frequency Range | 10 MHz- 18.0 GHz | |
| Power Output @ P1dB | 20 dBm Min | CW or Pulse |
| Linear Gain | 30 dB Typ | 0dBm or less for rated Pout |
| Power Gain Flatness | ±2.5 dB Max | Constant input power |
| Input Return Loss | -10 dB Max | |
| Noise Figure | 10 dB Max / 6dB Typ | |
| Harmonics | -20 dBc Typ | At rated output power |
| Spurious | -60 dBc Max | Non-harmonics |
| Operating Voltage | 100 - 240 VAC | 47-63 Hz |
| Power Consumption | 50 Watt Max | At rated output |
| Input Power Protection | +8 dBm Max | Without damage |
| Load VSWR Protection | ∞ : 1 | |

**ENVIRONMENTAL CHARACTERISTICS**

| Parameter | Specification | Notes |
|---|---|---|
| Operating Ambient Temperature | 0 to +50 ºC | |
| Storage Temperature | -40 to +70 ºC | |
| Relative Humidity | up to 95 % | Non Condensing |
| Altitude | 3000 meters | |
| Shock & Vibration | Normal transport | |


**MECHANICAL SPECIFICATIONS**

| Parameter | Specification | Notes |
|---|---|---|
| Dimensions W x H x D | 210 x 100 x 300 mm | Excluding brackets |
| Dimensions W x H x D (Benchtop) | 242 x 110 x 384 mm | Including brackets |
| Weight | 6 kg. | |
| RF Connectors In/Out | N Female or SMA Female | Front panel standard |
| AC Power / Interface Connector | IEC 60320-C14 / 9-Pin D-Sub | Or equivalent |
| Cooling | Built in Fan Cooling | |

**338 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877**
**www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com**
**Specifications subject to change without notice. Specifications and drawings may vary with selected options.**

# HD35284
# SOLID STATE MEDIUM POWER AMPLIFIER

## OUTLINE DRAWING




338 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com
Specifications subject to change without notice. Specifications and drawings may vary with selected options.