HD35286
SOLID STATE MEDIUM POWER AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all communication applications.
Small form factor, Bench Top system
Class A linear advanced technology design
Suitable for all single channel modulation standards
Instantaneous ultra-broad bandwidth
Built-in protection circuits
Universal voltage AC power supply
High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS : 50Ω, 25ºC

Parameter	Specification	Notes
Operating Frequency Range	50 - 6000 MHz	
Power Output @ P1dB	25 dBm Min	CW or Pulse
Linear Gain	30 dB Typ	0dBm or less for rated Pout
Power Gain Flatness	±2.0 dB Max	Constant input power
Input Return Loss	-10 dB Max	
Harmonics	-20 dBc Typ	At rated output power
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	47-63 Hz
Power Consumption	50 Watt Max	At rated output
Input Power Protection	+8 dBm Max	Without damage
Load VSWR Protection	∞ : 1	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 ºC	
Storage Temperature	-40 to +70 ºC	
Relative Humidity	up to 95 %	Non Condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport	


MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	210 x 100 x 300 mm	Excluding brackets
Dimensions W x H x D (Benchtop)	242 x 110 x 384 mm	Including brackets
Weight	6 kg.	
RF Connectors In/Out	N Female or SMA Female	Front panel standard
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	

338 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com
Specifications subject to change without notice. Specifications and drawings may vary with selected options.

HD35286
SOLID STATE MEDIUM POWER AMPLIFIER

OUTLINE DRAWING



338 Jericho Turnpike, Suite 387, Syosset NY, 11791 (631)-588-3877
www.rfamplifiers.com sales@hdcom.com. www.rfcomp.com
Specifications subject to change without notice. Specifications and drawings may vary with selected options.